

SY2L & SY4L SERIES LED WORK LIGHTS

TOTALSOURCE®

FEATURED PRODUCTS

Illuminator®

SY2L & SY4L Series

Specifications:

Voltage: 12-48VDC

Light Source: 2 or 4 LEDs

Light Output: 310 lumens/400 candela (2 LED models)

450 lumens/1000 candela (4 LED models)

Output: 4.5 Watts (2 LED models), 8.5 Watts (4 LED models)

Current Draw: .4AMP@12V & .1AMP@48V (2 LED models)

.9AMP@12V & .3AMP@48V (4 LED models)

Beam Pattern: Flood

Viewing Angle: 60°

Mounting Hardware: Stainless steel

Lens: Polycarbonate

Size: 3.67" Oval (2 LED model), Ø4.72" Round or 4.33" Square (4 LED model)

Mount: Pedestal, Pendant, Lateral RH or LH with stud swivel & wire leads

Operating Temperature: -40 to +65°C

Features:

- Thermal shock resistant
- Reverse polarity protected
- Spike protected
- 2 year warranty
- IP66

Certifications:

CE certified

UL pending (4 LED models only)



| Part # | Description |
|---------|--------------------------------|
| SY2LWLO | 12-48VDC Light, 2 LEDs, Oval |
| SY4LWLR | 12-48VDC Light, 4 LEDs, Round |
| SY4LWLS | 12-48VDC Light, 4 LEDs, Square |